

Shower Trailer Set-Up Procedures

1. Park trailer on a fairly level spot close to water, electrical, and sewer drain.
Using _ _ _ _ to open center door, remove step and place outside door. Chock Tires with rubber chocks in center room. Level is hanging on front bulkhead. Level trailer as needed, using 2X6s for side to side leveling. Use front jack to level length wise. There are four more support jacks. Front corners of trailer, use jack handle on floor of center room. On rear corners let jacks down, pin and use tapered blocks in front supply room closet. (_ _ _ _) (#2 shower)
Drive tapered blocks tight using hammer in tool box, center room.
_ _ _ _ *above represents the combination code. Please ask your instructor or supervisor for it.*
2. Using key ring from wall hook on right bulkhead, Black or Red keys unlock both locks on each door and place steps outside doors.
9. Using key from key ring unlock left outside doors to access water connection and propane line.
8. Remove freshwater hose and electrical cord and attach to supply from building. Turn on water and check for leaks. Open all faucets to remove air from water lines.
11. Move propane bottle from center room and place on left side next to trailer wheels, leave bottle attached to cart (see pictures) Remove propane regulator from front storage room and strap to propane bottle connection door.
12. Remove propane bottle and cart. Be sure to unlatch from wall and reattach ratchet strap to cart and bottle. (Two people are needed to remove bottle from control room.) Place bottle near regulator stand and attach regulator to bottle.
13. Attach propane line from inside trailer to regulator.
14. Make sure all valves on propane manifold are off.
15. Turn on propane bottle and check for any leaks using a spray bottle with soapy water.
16. Use chain and combination lock to secure propane bottle and regulator to trailer. (Chain thru trailer wheel)
17. Remove tank from center room, place under gray water drain left center of trailer, use short hose (in rear storage closet) to direct gray water into tank! See pictures in center room. Install pump into tank and use gray water garden hose to site drain. The pump switch can be difficult to hook up!! SEE PICTURES!! Check pump for debris on pump intake every ½ day or so.
18. Lock storage cabinet with combination lock.
19. Inside control room, turn on gas valve under on-demand hot water heater. Push the power on button on control unit on the wall, right of the on demand water heater. Temperature should be set at 120 degrees.
20. Turn on gas line to floor furnace and use the remote control that is stored inside the lid to operate furnace.